

STANDARD PRODUCT




Date: 08/13/2008

Prepared for: Production

Planetary Gearmotor

Model Number: MMP G15-24V GT-256



DC MOTOR PERFORMANCE PARAMETERS	Value	Units	Tolerance
RATED VOLTAGE D.C.	24.0	VOLTS	----
RATED CONTINUOUS CURRENT	0.80	AMPERE	----
RATED CONTINUOUS TORQUE	5.0	OZ - IN	----
RATED SPEED	4800	RPM	+/- 15%
RATED CONTINUOUS POWER OUT	17	WATTS	+/- 15%
NO LOAD SPEED	5200	RPM	MAX
NO LOAD CURRENT	0.17	AMPS	MAX
BACK EMF CONSTANT (Ke)	4.5	V/KRPM	+/- 10%
TORQUE CONSTANT (Kt)	6.1	OZ - IN / A	+/- 10%
DC ARMATURE RESISTANCE AT 1.5 AMPS	6.6	OHMS	+/- 15%
ARMATURE TEMP	155	DEGR. C	MAX
PEAK TORQUE (motor)	30	OZ - IN	----
PLANETARY GEARMOTOR OUTPUT PARAMETERS:			
PLANETARY GEARHEAD RATIO	256:1		
GEARHEAD RATED CONTINUOUS TORQUE	32.0	LB - IN	MAX
GEARHEAD RATED PEAK TORQUE	78.0++	LB - IN	MAX
GEARHEAD SHAFT OUTPUT SPEED (@ F.L.)	19	RPM	----
GEARMOTOR TOTAL LENGTH ("L" DIMENSION)	4.7	INCHES	MAX
GEARHEAD EFFICIENCY	41	%	
GEARMOTOR TOTAL WEIGHT	16	OUNCES	MAX

++ All Peak Torque Values are dependent upon duty. Kindly consult our Sales Offices for further details

~ MIDWEST MOTION PRODUCTS ~

Design, Manufacturing & Distribution — Motion Control Equipment

10761 Ahern Avenue S. E. Watertown, MN. 55388

Phone: 952-955-2626 Fax: 480-247-4096

www.midwestmotion.com

email: randy@midwestmotion.com