


**Model Number:****MMP BL87-435G-120V GP81-03.7**

DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	3.70 : 1		
Gearhead Shaft Output Speed (at full-load)	941	RPM	MAX
Gearmotor Rated Continuous Torque	36	In-Lbs	MAX
Gearmotor Rated Peak Torque	104++	In-Lbs	----
Gearhead Standard Backlash	30	Arc Minutes	MAX
Gearhead Efficiency	80%	----	----
Output Shaft Radial Load Capacity	90	Lbs	MAX
Output Shaft Axial Load Capacity	18	Lbs	MAX
Gearmotor Total Weight	11	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	120	DC VOLTS	----
Rated Continuous Current	6.0	AMPERES	----
No-Load Speed	4633	RPM	MAX
Rated Speed	3482	RPM	+/- 15%
Rated Continuous Power Out	502	WATTS	+/- 15%
Rated Continuous Torque	195	OZ-IN	----
Peak Torque (motor only)	564	OZ-IN	----
No-Load Current	0.44	AMPERES	MAX
Back EMF Constant (Ke)	25.9	V/KRPM	+/- 10%
Torque Constant (Kt)	35.0	OZ-IN/AMP	+/- 10%
DC Armature Resistance	4.97	OHMS	+/- 15%
Armature Inductance	2.84	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**www.midwestmotion.comemail: sales@midwestmotion.com