




**Model Number:****MMP BL58-487D-24V GP52-04.3**

| MOTOR LEADS |       |
|-------------|-------|
| LEAD        | COLOR |
| M1          | RED   |
| M2          | BLACK |
| M3          | WHITE |

| HALL LEADS |        |
|------------|--------|
| LEAD       | COLOR  |
| H1         | BLUE   |
| H2         | GREY   |
| H3         | VIOLET |
| VCC        | RED    |
| GND        | BLACK  |



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| PLANETARY GEARMOTOR OUTPUT PARAMETERS:     | VALUE    | UNITS       | TOLERANCE |
|--------------------------------------------|----------|-------------|-----------|
| Gearhead Ratio (exact)                     | 4.28 : 1 |             |           |
| Gearhead Shaft Output Speed (at full-load) | 662      | RPM         | MAX       |
| Gearmotor Rated Continuous Torque          | 23       | In-Lbs      | MAX       |
| Gearmotor Rated Peak Torque                | 66++     | In-Lbs      | ----      |
| Gearhead Standard Backlash                 | 42       | Arc Minutes | MAX       |
| Gearhead Efficiency                        | 80%      | ----        | ----      |
| Output Shaft Radial Load Capacity          | 45       | Lbs         | MAX       |
| Output Shaft Axial Load Capacity           | 14       | Lbs         | MAX       |
| Gearmotor Total Weight                     | 3.8      | Lbs         | MAX       |

**++ All Peak Torque values are dependent upon duty. Contact our sales office for details.**

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS     | TOLERANCE |
|----------------------------------|-------|-----------|-----------|
| Rated DC Voltage                 | 24    | DC VOLTS  | ----      |
| Rated Continuous Current         | 13.0  | AMPERES   | ----      |
| No-Load Speed                    | 3750  | RPM       | MAX       |
| Rated Speed                      | 2833  | RPM       | +/- 15%   |
| Rated Continuous Power Out       | 225   | WATTS     | +/- 15%   |
| Rated Continuous Torque          | 107   | OZ-IN     | ----      |
| Peak Torque (motor only)         | 307   | OZ-IN     | ----      |
| No-Load Current                  | 0.64  | AMPERES   | MAX       |
| Back EMF Constant (Ke)           | 6.4   | V/KRPM    | +/- 10%   |
| Torque Constant (Kt)             | 8.7   | OZ-IN/AMP | +/- 10%   |
| DC Armature Resistance           | 0.45  | OHMS      | +/- 15%   |
| Armature Inductance              | 0.37  | mH        | +/- 15%   |
| Armature temperature             | 155   | DEG. C    | MAX       |

**NOTES:**

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

**MIDWEST MOTION PRODUCTS****DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**[www.midwestmotion.com](http://www.midwestmotion.com)email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)