




REVERSIBLE BRUSHLESS DC RIGHT-ANGLED GEARMOTOR

Model Number:

MMP BL86-425D-24V GRA81-029



PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	28.93 : 1		
Gearhead Shaft Output Speed (at full-load)	124	RPM	MAX
Gearmotor Rated Continuous Torque	168	In-Lbs	MAX
Gearmotor Rated Peak Torque	429++	In-Lbs	----
Gearhead Standard Backlash	33	Arc Minutes	MAX
Gearhead Efficiency	75%	----	----
Output Shaft Radial Load Capacity	135	Lbs	MAX
Output Shaft Axial Load Capacity	27	Lbs	MAX
Gearmotor Total Weight	13	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	24	DC VOLTS	----
Rated Continuous Current	20.5	AMPERES	----
No-Load Speed	5000	RPM	MAX
Rated Speed	3595	RPM	+/- 15%
Rated Continuous Power Out	330	WATTS	+/- 15%
Rated Continuous Torque	124	OZ-IN	----
Peak Torque (motor only)	316	OZ-IN	----
No-Load Current	1.39	AMPERES	MAX
Back EMF Constant (Ke)	4.8	V/KRPM	+/- 10%
Torque Constant (Kt)	6.5	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.33	OHMS	+/- 15%
Armature Inductance	0.27	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com