




MMP BL86-425F-36V GRA81-236



DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	36	DC VOLTS	----
Rated Continuous Current	14.9	AMPERES	----
No-Load Speed	4675	RPM	MAX
Rated Speed	3159	RPM	+/- 15%
Rated Continuous Power Out	343	WATTS	+/- 15%
Rated Continuous Torque	147	OZ-IN	----
Peak Torque (motor only)	320	OZ-IN	----
No-Load Current	0.86	AMPERES	MAX
Back EMF Constant (Ke)	7.7	V/KRPM	+/- 10%
Torque Constant (Kt)	10.4	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.78	OHMS	+/- 15%
Armature Inductance	0.69	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

email: sales@midwestmotion.com