




REVERSIBLE BRUSHED DC MOTOR

Model Number:

MMP D22-301D-24V



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	24	DC VOLTS	----
Rated Continuous Current	4.4	AMPERES	----
No-Load Speed	7500	RPM	MAX
Rated Speed	5590	RPM	+/- 15%
Rated Continuous Power Out	63	WATTS	+/- 15%
Rated Continuous Torque	15	OZ-IN	----
Peak Torque (motor only)	50	OZ-IN	----
No-Load Current	0.84	AMPERES	MAX
Back EMF Constant (Ke)	3.2	V/KRPM	+/- 10%
Torque Constant (Kt)	4.3	OZ-IN/AMP	+/- 10%
DC Armature Resistance	1.39	OHMS	+/- 15%
Armature Inductance	1.23	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com