


**Model Number:****MMP S14-247D-12V GP32-014**

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	13.73 : 1		
Gearhead Shaft Output Speed (at full-load)	262	RPM	MAX
Gearmotor Rated Continuous Torque	5.1	In-Lbs	MAX
Gearmotor Rated Peak Torque	14++	In-Lbs	----
Gearhead Standard Backlash	93	Arc Minutes	MAX
Gearhead Efficiency	75%	----	----
Output Shaft Radial Load Capacity	16	Lbs	MAX
Output Shaft Axial Load Capacity	5	Lbs	MAX
Gearmotor Total Weight	1.1	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	12	DC VOLTS	----
Rated Continuous Current	3.25	AMPERES	----
No-Load Speed	5217	RPM	MAX
Rated Speed	3590	RPM	+/- 15%
Rated Continuous Power Out	21	WATTS	+/- 15%
Rated Continuous Torque	8.0	OZ-IN	----
Peak Torque (motor only)	22	OZ-IN	----
No-Load Current	0.68	AMPERES	MAX
Back EMF Constant (Ke)	2.3	V/KRPM	+/- 10%
Torque Constant (Kt)	3.1	OZ-IN/AMP	+/- 10%
DC Armature Resistance	1.15	OHMS	+/- 15%
Armature Inductance	0.16	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT****www.midwestmotion.com****email: sales@midwestmotion.com**