




**Model Number:**

**MMP D33-455G-48V GP81-1140**



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| PLANETARY GEARMOTOR OUTPUT PARAMETERS:     | VALUE       | UNITS       | TOLERANCE |
|--------------------------------------------|-------------|-------------|-----------|
| Gearhead Ratio (exact)                     | 1139.73 : 1 |             |           |
| Gearhead Shaft Output Speed (at full-load) | 3.3         | RPM         | MAX       |
| Gearmotor Rated Continuous Torque          | 2125        | In-Lbs      | MAX       |
| Gearmotor Rated Peak Torque                | 2125++      | In-Lbs      | ----      |
| Gearhead Standard Backlash                 | 39          | Arc Minutes | MAX       |
| Gearhead Efficiency                        | 65%         | ----        | ----      |
| Output Shaft Radial Load Capacity          | 293         | Lbs         | MAX       |
| Output Shaft Axial Load Capacity           | 63          | Lbs         | MAX       |
| Gearmotor Total Weight                     | 14          | Lbs         | MAX       |

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS     | TOLERANCE |
|----------------------------------|-------|-----------|-----------|
| Rated DC Voltage                 | 48    | DC VOLTS  | ----      |
| Rated Continuous Current         | 3.47  | AMPERES   | ----      |
| No-Load Speed                    | 4103  | RPM       | MAX       |
| Rated Speed                      | 3721  | RPM       | +/- 15%   |
| Rated Continuous Power Out       | 126   | WATTS     | +/- 15%   |
| Rated Continuous Torque          | 46    | OZ-IN     | ----      |
| Peak Torque (motor only)         | 393   | OZ-IN     | ----      |
| No-Load Current                  | 0.56  | AMPERES   | MAX       |
| Back EMF Constant (Ke)           | 11.7  | V/KRPM    | +/- 10%   |
| Torque Constant (Kt)             | 15.8  | OZ-IN/AMP | +/- 10%   |
| DC Armature Resistance           | 1.29  | OHMS      | +/- 15%   |
| Armature Inductance              | 0.90  | mH        | +/- 15%   |
| Armature temperature             | 155   | DEG. C    | MAX       |

**NOTES:**

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

## MIDWEST MOTION PRODUCTS

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

[www.midwestmotion.com](http://www.midwestmotion.com)

email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)