


Model Number:

MMP S40-775I-60V GP105-068



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	68.06 : 1		
Gearmotor Output Speed (at Cont. Torque)	27	RPM	+/- 15%
Gearmotor Rated Continuous Torque	1042	In-Lbs	MAX
Gearmotor Peak Torque Capacity	3452++	In-Lbs	MAX
Gearhead Standard Backlash	39	Arc Minutes	MAX
Gearhead Efficiency	70%	----	----
Output Shaft Radial Load Capacity	338	Lbs	MAX
Output Shaft Axial Load Capacity	68	Lbs	MAX
Gearmotor Total Weight	14.5	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Input DC Voltage	60	DC VOLTS	----
No-Load Current	0.83	AMPERES	MAX
No-Load Speed	1909	RPM	+/- 15%
Rated Continuous Torque	350	OZ-IN	MAX
Rated Continuous Current	9.1	AMPERES	MAX
Rated Speed (at Cont. Torque)	1838	RPM	+/- 15%
Rated Continuous Power Out	476	WATTS	+/- 15%
Peak Motor Torque	1159	OZ-IN	MAX
Peak Motor Current	28.2	AMPERES	MAX
Back EMF Constant (Ke)	31.3	V/KRPM	+/- 10%
Torque Constant (Kt)	42.3	OZ-IN/AMP	+/- 10%
DC Armature Resistance	0.30	OHMS	+/- 15%
Armature Inductance	0.79	mH	+/- 15%
Number of Motor Poles	4	(-)	----
Armature temperature	155	DEG. C	MAX

NOTES:


1. Rated speeds may drop as the motor temperature increases. Values are stated with the motor at 25 °C.
2. All Peak Torque values are dependent upon duty. Contact our sales office for details.

ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

GEARMOTOR CURRENT-TORQUE

MMP S40-775I-60V GP105-068



GEARMOTOR SPEED-TORQUE

MMP S40-775I-60V GP105-068

