


Model Number:
MMP D33-455K-90V GP81-005


DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

PLANETARY GEARMOTOR OUTPUT PARAMETERS:	VALUE	UNITS	TOLERANCE
Gearhead Ratio (exact)	5.18 : 1		
Gearhead Shaft Output Speed (at full-load)	485	RPM	MAX
Gearmotor Rated Continuous Torque	25	In-Lbs	MAX
Gearmotor Rated Peak Torque	93++	In-Lbs	----
Gearhead Standard Backlash	30	Arc Minutes	MAX
Gearhead Efficiency	80%	----	----
Output Shaft Radial Load Capacity	90	Lbs	MAX
Output Shaft Axial Load Capacity	18	Lbs	MAX
Gearmotor Total Weight	10.0	Lbs	MAX

++ All Peak Torque values are dependent upon duty. Contact our sales office for details.

DC MOTOR PERFORMANCE PARAMETERS:	VALUE	UNITS	TOLERANCE
Rated DC Voltage	90	DC VOLTS	----
Rated Continuous Current	2.68	AMPERES	----
No-Load Speed	3114	RPM	MAX
Rated Speed	2510	RPM	+/- 15%
Rated Continuous Power Out	178	WATTS	+/- 15%
Rated Continuous Torque	96	OZ-IN	----
Peak Torque (motor only)	360	OZ-IN	----
No-Load Current	0.23	AMPERES	MAX
Back EMF Constant (Ke)	28.9	V/KRPM	+/- 10%
Torque Constant (Kt)	39.1	OZ-IN/AMP	+/- 10%
DC Armature Resistance	6.51	OHMS	+/- 15%
Armature Inductance	5.61	mH	+/- 15%
Armature temperature	155	DEG. C	MAX

NOTES:

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS
DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT
www.midwestmotion.com

 email: sales@midwestmotion.com