


**Model Number:**

**MMP D33-655F-36V GRA81-029**



DIMENSIONS ARE INCHES [MM] UNLESS OTHERWISE STATED

| PLANETARY GEARMOTOR OUTPUT PARAMETERS:     | VALUE        | UNITS       | TOLERANCE |
|--|--------------|-------------|-----------|
| Gearhead Ratio (exact)                     | 28.93 : 1    |             |           |
| Gearhead Shaft Output Speed (at full-load) | 73           | RPM         | MAX       |
| Gearmotor Rated Continuous Torque          | 191          | In-Lbs      | MAX       |
| Gearmotor Rated Peak Torque                | <b>771++</b> | In-Lbs      | ----      |
| Gearhead Standard Backlash                 | 33           | Arc Minutes | MAX       |
| Gearhead Efficiency                        | 75%          | ----        | ----      |
| Output Shaft Radial Load Capacity          | 135          | Lbs         | MAX       |
| Output Shaft Axial Load Capacity           | 27           | Lbs         | MAX       |
| Gearmotor Total Weight                     | 17           | Lbs         | MAX       |

**++ All Peak Torque values are dependent upon duty. Contact our sales office for details.**

| DC MOTOR PERFORMANCE PARAMETERS: | VALUE | UNITS     | TOLERANCE |
|----------------------------------|-------|-----------|-----------|
| Rated DC Voltage                 | 36    | DC VOLTS  | ----      |
| Rated Continuous Current         | 8.0   | AMPERES   | ----      |
| No-Load Speed                    | 2553  | RPM       | MAX       |
| Rated Speed                      | 2098  | RPM       | +/- 15%   |
| Rated Continuous Power Out       | 219   | WATTS     | +/- 15%   |
| Rated Continuous Torque          | 141   | OZ-IN     | ----      |
| Peak Torque (motor only)         | 568   | OZ-IN     | ----      |
| No-Load Current                  | 0.57  | AMPERES   | MAX       |
| Back EMF Constant (Ke)           | 14.1  | V/KRPM    | +/- 10%   |
| Torque Constant (Kt)             | 19.1  | OZ-IN/AMP | +/- 10%   |
| DC Armature Resistance           | 0.81  | OHMS      | +/- 15%   |
| Armature Inductance              | 0.54  | mH        | +/- 15%   |
| Armature temperature             | 155   | DEG. C    | MAX       |

**NOTES:**

- ENCODER & BRAKE OPTIONS AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)
- NEMA MOUNTING FLANGE OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

**MIDWEST MOTION PRODUCTS, INC**

**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**

[www.midwestmotion.com](http://www.midwestmotion.com)

email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)