




Model Number:

**MMP LA3-12V-20-A-150**


# **DC LINEAR ACTUATOR**

- IP65 INGRESS PROTECTION
- BUILT-IN LIMIT SWITCHES AT EACH END OF TRAVEL
- ACME SCREW (ANTI-BACKDRIVING)
- NON-ROTATING ALUMINUM INNER TUBE



| PERFORMANCE PARAMETERS                       | VALUE       | UNITS           | TOLERANCE |
|----------------------------------------------|-------------|-----------------|-----------|
| Rated DC Voltage                             | 12          | VDC             | ----      |
| Gear Ratio                                   | 20:1        | ----            | ----      |
| Rated Force Capacity                         | 112 (500)   | LBS (N)         | MAX       |
| Rated Current (at rated force capacity)      | 3.2         | AMPERES         | MAX       |
| Rated Stroke Speed (at rated force capacity) | 0.48 (12.2) | IN/SEC (MM/SEC) | ± 10%     |
| Stroke Speed at No-Load                      | 0.57 (14.5) | IN/SEC (MM/SEC) | ± 10%     |
| Static Load Capacity                         | 562 (2500)  | LBS (N)         | MAX       |
| Maximum Recommended Duty                     | 25%         | ----            | MAX       |
| Minimum Ambient Operating Temperature Range  | -13 (-25)   | °F (C)          | MIN       |
| Maximum Ambient Operating Temperature Range  | 149 (65)    | °F (C)          | MAX       |

## **PERFORMANCE CURVES:**



• OPTIONAL MOUNTING BRACKET OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

**MIDWEST MOTION PRODUCTS, INC**

**DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT**

[www.midwestmotion.com](http://www.midwestmotion.com)

email: [sales@midwestmotion.com](mailto:sales@midwestmotion.com)