




Model Number:

MMP LA3-24V-5-A-200-P


DC LINEAR ACTUATOR

- IP65 INGRESS PROTECTION
- BUILT-IN LIMIT SWITCHES AT EACH END OF TRAVEL
- ACME SCREW (ANTI-BACKDRIVING)
- NON-ROTATING ALUMINUM INNER TUBE



PERFORMANCE PARAMETERS	VALUE	UNITS	TOLERANCE
Rated DC Voltage	24	VDC	----
Gear Ratio	5:1	----	----
Rated Force Capacity	34 (150)	LBS (N)	MAX
Rated Current (at rated force capacity)	1.6	AMPERES	MAX
Rated Stroke Speed (at rated force capacity)	1.44 (36.6)	IN/SEC (MM/SEC)	± 10%
Stroke Speed at No-Load	1.73 (43.9)	IN/SEC (MM/SEC)	± 10%
Static Load Capacity	562 (2500)	LBS (N)	MAX
Maximum Recommended Duty	25%	----	MAX
Minimum Ambient Operating Temperature Range	-13 (-25)	°F (C)	MIN
Maximum Ambient Operating Temperature Range	149 (65)	°F (C)	MAX
Actuator Resistance Stroke Range (BLU-WHT)	9.6	kΩ	± 1
Actuator Full Resistance (YLW - WHT)	10	kΩ	± 0.5

PERFORMANCE CURVES:



• OPTIONAL MOUNTING BRACKET OPTION AVAILABLE – [FOLLOW THIS LINK FOR DETAILS](#)

MIDWEST MOTION PRODUCTS, INC

DESIGN, MANUFACTURING & DISTRIBUTION - MOTION CONTROL EQUIPMENT

www.midwestmotion.com

email: sales@midwestmotion.com